

TDS20110

DECT phone for AURUS-TFT (Wireless)



The TDS20110 DECT phone is the ideal partner to be used in combination with the AURUS-TFT which results in a complete indoor unit for video-door-phone application. Therefore the door-phone system needs to be provided with a standard analog 'a-b' phone connection (for this DECT-phone).

The TDS20110 telephone is one of the smallest analogue design phones on the market and gives ease of use with the keyboard positioned under the handset. The head is elegantly lifted into your hand by lightly pushing on the upper part. It is equipped with 2 direct memory keys, 10 secondary memory keys, a last number redial and a mute function. The ring tone can be switched from high to low. The phone is meant to be wall mounted next to the AURUS-TFT touch screen.

Color: Anthracite / Silver

Application:	DECT telephone for use in combination with AURUS-TFT as indoor video-door phone set.	
Characteristics:	12 hours talk time, 7 days standby time, GAP compatible. Indoor range: max. 20 m Pan-European approved EN55022 and EN55024	
Installation:	Wall mounting	
Connections:	PABX Mains	a-b connection (analog telephone) 230VAC
Dimensions:	Unit Packing	200H x 44W x 50D 257H x 130W x 75D
Net Gross Weight:	0,310kg (base) + 0,140kg (hook) + 0,140kg (mains adaptor) 0,990kg	
Packaging content:	Telephone handset + Base station + Table stand RJ-11 cable 3m Li-ion 3,7V 650mAh rechargeable battery Mains adaptor 230VAC	
Operation range:	Temperature Relative humidity	0°C to +30°C max. 5% to 80% at 25°C (no humidity/condense)
Limited warranty:	2 years	

Schematic Drawing:

