

TDS20620

DALI-address programming tool



DALI-address programming tool for System Integrators.

With this tool you can address any of the individual connected DALI ballasts (address 0 to 63).

To be used together with TDS13620 TELETASK DALI Interface.

APPLICATION

Addressing tool for DALI ballasts.

CHARACTERISTICS

General

Software addressing of DALI compatible ballasts.

SETTINGS

Configuration

Use configuration software of the included mini CD-rom.

INSTALLATION

Mounting

Wall mount

Unit power supply

USB (from PC)

DALI power supply

TDS13620 interface

CONNECTION

PC

USB interface

DALI

DALI bus

POWER CONSUMPTION

<0,1W (TDS20620)

DIMENSIONS

132 W x 71 H x 25 D (mm)

NET | PACKED WEIGHT

0,135 kg | 0,280 kg

PACKAGING CONTENT

- 1x TDS20620 tool
- 1x USB cable
- 1x mini CD-rom
- 1x Installation manual

STORAGE

Temperature

-20°C to +65°C

Relative humidity

15% to 85%

IP PROTECTION RATE

IP30

OPERATING RANGE

Temperature

From 0°C to +60°C

Relative humidity

5% to 80% at 25°C (no humidity/condense)

SCHEMATIC DRAWING

TDS20620

