



**TDS56421B**

**Demo case NANOS**

This democase is intended to be used for:

- Practicing the configuration of a TELETASK System
- Basic training about cabling and connecting
- Commercial demo, including wireless GUI's (Graphical User interfaces) on PC, Smartphone, iPhone and iPod Touch.
- Exercises and demo of the integration of IP camera's on the GUI's (built-in Wi-Fi router + IP-camera)

The case contains an illustrated presentation panel, technical interfaces, AURUS-4, AURUS-OLED, light sensor...

The mains cord is the only connection you have to make for a complete PROSOFT and GUI demo.

**APPLICATION**

Training, demo, programming practice.

**CHARACTERISTICS**

**Mechanical**

Ruggedized case with technical interfaces, presentation panel and large top compartment for documents, samples etc.

**Electrical**

Plug-in connector for 100-240VAC power cord.  
The mains adapter of the Wi-Fi router only suited for 230V application (internally connected; can be exchanged by customer).

**Content**

- TDS10200 NANOS Central Unit
- TDS10130 Power Supply
- TDS12021 AURUS-4
- TDS12022 AURUS-OLED
- TDS12116 Digital input interface
- TDS12270 Light sensor
- TDS12309 Analog input interface
- TDS12502 Remote control
- TDS13510 Relais interface
- TDS13525 DC Motor interface
- TDS13609 Dimmer interface
- TDS15101 Licence for iSGUI (mobile phone)
- TDS15105 Licence for GUI+ (PC)
- Wi-Fi access point
- IP- colour camera

**INSTALLATION**

Carry case – Ready to use.

**CONNECTIONS**

**Electrical**

Plug-in connector for 110/230V power supply cord.

**LAN**

WIFI access point on board.

**DIMENSIONS**

600 x 450 x 220 mm

**NET | GROSS WEIGHT**

12.7 | 13 kg

**STORAGE**

**Temperature**

-20°C to +65°C

**Relative humidity**

15% to 85%

**IP PROTECTION RATE**

IP20

**OPERATING RANGE**

**Temperature**

0°C to +50°C max.

**Relative humidity**

5% to 80% at 25°C (non-condensing ambient)

**SCHEMATIC DRAWING**

