TDS14260 CHORUS 260 audio streamer- amplifier 120W

CHORUS 260 is a sophisticated all-in-one streamer stereo amplifier (120W) that combines sleek design with powerful performance. Enjoy effortless streaming, rich room-filling sound, and intuitive controls designed for modern living and uncompromising audio quality in one elegant device.
CHORUS 260 lets you work with external speakers of your choice: both in-wall speakers and speaker boxes. Quality and budget are free to choose, which is an advantage over streamers with built-in speakers.
Hi-Fi quality in an extremely compact unit for stand-alone, multi-room and in TELETASK-integrated installations. Control of audio from an app and/or via the TDS buttons and touch screens for lighting, HVAC, blinds, etc. This integration ensures an extremely calm and harmonious interior compared to separate control panels.

APPLICATION

Centrally installed audio solution. A local (stand-alone) application is also possible, where you place the CHORUS in the room itself. Ideal for children's rooms and all spaces where you want to have everything in hand locally.

CHARACTERISTICS

General

Streamer unit with built-in power amplifier. Black aluminium housing with large volume rotary knob. LAN connection via wired Ethernet or Wi-Fi.
CHORUS 260 also has an analogue audio input and a volume-controlled output for connection to an external source and amplifier (e.g. an active bass unit).
For local setup (in a room), there is also a volume dial with source selection on the front of the device. Most functions (including bass and treble setting) can also be set via the supplied IR remote control. A USB-A input and Bluetooth support are also present.

Supported Losless audio formats:
MP3/WMA/AAC/AAC+/ALAC /FLAC/APE/WAV
Supported streaming sources: Airplay, Spotify, Amazon music, TuneIn, Tidle, Qobuz, Pandora, Napster, …
Audio sampling: up to 192KHz – 24 bit.

Control apps: WiiM (recommended), 4Stream, ...
Integration with TELETASK TDS: via LAN (no audio license required).

Indication LED

Status indicator (check the user manual for more details)

SETTINGS

Configuration

The settings are configured in the PROSOFT Suite (V5.0.266 or higher).
Maximum 25 x CHORUS 260 coupled with TDS.
See the user manual for configuration details (also downloadable from the teletask.be site chapter Downloads)

INSTALLATION

Placement

Placement on a horizontal plane. Multiple devices can be placed on and/or next to each other. Only place horizontally = cooling fin horizontal. Never place the CHORUS 260 unit on its side!

Power supply

24VDC/5A power supply (supplied with the unit).

Important note on installation:

! Only place the device horizontally. Never vertically.

CONNECTIONS

Ethernet

LAN via RJ45 connector (Ethernet 100Mb)
LAN can also be via Wi-Fi (2.4GHz)

Input

Analogue audio input with 2 x RCA connectors.
Bluetooth (5.2; up to 15m distance)
USB-A input (up to 64GB).
Built-in IR receiver for the included IR remote control (2 x AAA batteries not included)

Output

2 x 2 screw terminals for the speakers (max 4mm² / 12AWG).
External speakers (not included): 2 x 60W @ 4 ohm (impedance 4 to 16 ohm).
20Hz - 20KHz

POWER CONSUMPTION

Max. peak of the power supply: 2.4A (100-240VAC)

DIMENSIONS

120W x 52H x 160D (mm) – including antennas and volume knob

NET | GROSS WEIGHT

1.1 kg | 1.25 kg

PACKAGING CONTENT

TDS14260 interface
Power adapter: input 100-240VAC; output 24VDC/2.5A
IR remote control (2 x AAA batteries not included)
2 x antenna
Speaker screw connector 2x2 (max 4 mm2 / 12AWG)
User manual

ENVIRONMENTAL CONDITIONS

Storage (with no condensation or icing)

Temperature: -20°C to +65°C max.
Relative humidity: 5% to 85% max.

Operation (with no condensation or icing)

Temperature: 0°C to +50°C max.
Relative humidity: 5% to 80% max.

IP PROTECTION RATE

IP20

LIMITED WARRANTY

2 years

SCHEMATIC DRAWING

TELETASK can't be responsible for potential errors in the data sheets and technical documentation. Changes in the product features can be made at any time, without prior notice