



TDS14301

PORTUS MINI outdoor video door phone

The PORTUS MINI is a compact and discreet outdoor video door phone station for access control and communication at doors, gates and other types of entrances. This device supports SIP VoIP communication and enables hands-free audio and video contact with an indoor station (TELETASK- OPUS, - MAIOR or third-party VoIP SIP compatible indoor station). Thanks to the simple PoE Ethernet connection, the built-in tag reader, the night light and the status LEDs, the PORTUS MINI offers an easy-to-use and reliable solution. Multiple devices can be used within one project.

The PORTUS MINI can be used both within the TELETASK-system and stand-alone with a suitable SIP-VoIP indoor screen. Due to its compact design, the device is ideal for applications where seamless integration and efficient access control are important.

APPLICATION

Discreet, compact video door phone for residential and professional installations. It can be used both within TELETASK-installations and independently in a VoIP SIP environment. An external SIP server may be needed.

CHARACTERISTICS

General

Compact outdoor unit, equipped with a call button, integrated night lighting and a tag reader for automatic access (tags not included; order TDS12208 /5 pieces).

There is a built-in tamper alarm, triggered when the unit is removed from its wall bracket.

Indication LEDs

- Call is active
- Ongoing conversation
- Door open

SETTINGS

Configuration

Via LAN browser on the device's built-in server

INSTALLATION

On any flat wall where the mounting plate can be screwed in place, and where the Ethernet cable and any optional wiring can be brought in. See the connection diagram/installation manual.

Power supply

PoE 16 Watt (IEEE 802.3af).

CONNECTIONS

See the diagram below and the included installation manual for more details (can also be downloaded from teletask.be/downloads)

Contact inputs

2 x potential-free contact inputs for unlocking the door from the inside (push button / motion detector).

Contact outputs

Contact output (Change Over) for the door opener when using the internal tag reader.

POWER CONSUMPTION

Max. 16 Watt on PoE

DIMENSIONS

Without rain hood: 130 high x 50 wide x 29 deep (mm)

With rain hood: 137 high x 55 wide x 42 deep (mm)

NET | GROSS WEIGHT

0.15 kg | 0.35 kg

PACKAGING CONTENT

TDS14301 PORTUS MINI video door phone

Rain hood

Mounting plate with accessories

Connector set for optional connections

ENVIRONMENTAL CONDITIONS

Storage (with no condensation or icing)

Temperature: -40°C to +65°C max.

Relative humidity: 10% to 90% max.

Operation (with no condensation or icing)

Temperature: -40°C to +50°C max.

Relative humidity: 10% to 90% max.

IP PROTECTION RATE

IP65

LIMITED WARRANTY

2 years

SCHEMATIC DRAWING

